

## Coiled Metal Batten Strip

TIS #1201

ITEM NUMBER: **W56RAC3052**

**Description:**

Coiled Metal Batten Strip is specifically designed to be used for anchoring Firestone membranes and flashing details as specified in Firestone Specifications and Details. Coiled Metal Batten Strip is packaged in a weather-resistant cardboard dispensing package which contains 220 ft (67 m) of batten strip. Using Coiled Metal Batten Strips in lieu of conventional pre-cut strips reduces labor and storage space. Coiled Metal Batten Strip has 3" (76.2 mm) o.c. pre-punched holes for greater flexibility in attaching to steel decks.



**Method of Application:**

1. Attach batten strips to the roof substrate or penetration using the appropriate Firestone fastener. Do not overdrive or underdrive fasteners. Start at one end of the batten strip and fasten towards the other to reduce bowing between fasteners.

**Storage:**

- Store in original unopened containers protected from the weather.

**Precautions:**

- When cutting battens, round ends and remove burrs and sharp edges with a file.

**Compliance:**

Post Consumer Recycled Content: 8%  
 Pre Consumer Recycled Content: 17%  
 Manufacturing Location: Cleveland, OH



Packaging:	
Coil	220'
Coils per Pallet	52

Physical Properties:	Minimum Performance
Material	Galvalume® AZ 55
Corrosion Resistance	Meets FM No. 4470 criteria
Length	220' (67 m) per coil
Width	1.0" (25.4 mm)
Thickness	0.0448"/0.0508" (1.13 mm/1.29 mm)
Holes	0.344" (8.74 mm) diameter, at 3" (76.2 mm) o.c. (Accommodates Firestone All-Purpose, Heavy-Duty, Heavy-Duty Plus and Concrete Drive Fasteners)
Weight	32 lb (14.5 kg) per coil

Galvalume® is a registered trademark of BIEC International, Inc.

Please Contact your Firestone Technical Coordinator at 1-800-428-4511 for further information.

*This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.*