

TECHNICAL INFORMATION SHEET

Polymer Fastener Metal Batten Strip

TIS #1204

ITEM NUMBER: W56RAC3059

Description:

Polymer Fastener Metal Batten Strip is specifically designed to be used with the Firestone Polymer Fastener for anchoring Firestone membranes as specified in Firestone Specifications and Details.



Method of Application:

1. Polymer Fastener Metal Batten Strips are to be installed with "UP" side showing and as specified by Firestone Specifications and Details. Attach batten strips to roof substrate using the appropriate length Polymer Fastener.

Storage:

- Store in original unopened containers protected from the weather.

Precautions:

- All cut surfaces must be rounded and filed to remove burrs and sharp edges.
- Do not overdrive or underdrive fastener.

Compliance:

Post Consumer Recycled Content: 8%
Pre Consumer Recycled Content: 17%
Manufacturing Location: Cleveland, OH



Packaging:

Tube	50 – 10' (3.05 m) pieces per tube
------	-----------------------------------

Physical Properties:

Minimum Performance

Material	Galvalume® sheet steel
Corrosion Resistance	Meets FM No. 4470 criteria
Length	10' (3.05 m)
Width	1-1/4" (31.6 mm)
Thickness	0.0448"-0.0508"(1.13 mm-1.29 mm)
Holes	0.625" (15.9 mm) diameter, 21 @ 6" (152.4 mm) o.c. with 12 Teeth equally spaced around the hole. The teeth provide backout resistance when used with the Firestone Polymer Fastener.

Galvalume® is a registered trademark of BIEC International, Inc.

Please Contact your Firestone Technical Coordinator at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.