



- NOTES**
1. REFER TO FIRESTONE WEBSITE FOR THE MOST CURRENT INFORMATION.
 2. HOLE IN MEMBRANE SHOULD EXTEND A MINIMUM OF 1/2" (13 mm) BEYOND CLAMPING RING AND SHOULD NOT BE SMALLER THAN THE DIAMETER OF THE LEADER PIPE.
 3. INSULATION ADJACENT TO DRAIN TO BE APPROPRIATE FIRESTONE INSULATION WITH APPROPRIATE BONDING SURFACE.
 4. FIRESTONE WATERBLOCK MIN. OF 1/2 OF 10 OZ (295ML) TUBE PER 4" DRAIN. USE ADDITIONAL WATERBLOCK FOR LARGER DRAINS.
 5. IN REROOF APPLICATIONS:
 - REMOVE EXISTING FLASHING DOWN TO METAL BOWL.
 - REPAIR OR REPLACE BROKEN DRAIN COMPONENTS.
 - DRILL AND TAP BROKEN DRAINS BOLTS AND REPLACE IF NECESSARY.

MAXIMUM WARRANTY: **20 YEARS**

ROOF DRAIN WITH STEEP SLOPE SUMP

RUBBERGARD™ EPDM

ACCEPTABLE SYSTEMS: ALL

ISSUE /REVISION
DATE:
07/08/2014

DETAIL NO.

D-4