



- NOTES:
1. REFER TO FIRESTONE WEBSITE FOR MOST CURRENT INFORMATION.
 2. COMPRESSIBLE TUBE (SUPPLIED BY OTHERS) DIAMETER MUST EXCEED THE DECK OPENING BY 50% MIN. OR DESIGNED MOVEMENT (WHICH EVER IS GREATER).
 3. BATTEN STRIPS MAY BE USED IN LIEU OF 2" METAL PLATES FOR MAS AND FULLY ADHERED SYSTEMS ONLY. REFER TO "BT" DETAILS FOR SPECIFIC BASE TIE-IN INFORMATION, REQUIREMENTS AND OPTIONS.
 4. BONDING ADHESIVE REQUIRED BETWEEN MEMBRANE AND INSULATION FOR FULLY ADHERED SYSTEMS.
 5. MAXIMUM 6" (152 mm) LONG FASTENERS. (NOTE: WOOD BLOCKING MAY BE SUBSTITUTED FOR INSULATION TO REDUCE FASTENER LENGTH REQUIREMENTS).
 6. REFER TO LS-13 FOR ADDITIONAL LAP SPLICE REQUIREMENTS.

MAXIMUM WARRANTY: **20 YEARS**

Firestone
 BUILDING PRODUCTS
 NOBODY COVERS YOU BETTER.[™]
 www.firestoneppco.com

EXPANSION JOINT (FIELD FABRICATED) WITH QUICKSEAM SPLICE TAPE - ROOF TO ROOF

RUBBERGARD[™] EPDM

ACCEPTABLE SYSTEMS: ADHERED, RMAS

ISSUE / REVISION DATE: 07/08/2014

DETAIL NO. **E-6**

NOT TO SCALE