



- NOTES:
1. REFER TO FIRESTONE WEBSITE FOR MOST CURRENT INFORMATION.
 2. MAXIMUM 6" (152 mm) LONG FASTENERS. (NOTE: WOOD BLOCKING MAY BE SUBSTITUTED FOR INSULATION TO REDUCE FASTENER LENGTH REQUIREMENTS.)
 3. IN CASE OF OBSTRUCTION REFER TO DETAIL UT-BT-6.
 4. REFER TO UT-BT-14 & UT-BT-15 FOR QUICKSEAM RPF STRIP LAYOUT AT CORNERS.
 5. BONDING ADHESIVE REQUIRED BETWEEN MEMBRANE AND INSULATION FOR FULLY ADHERED SYSTEMS.
 6. BATTEN STRIPS MAY BE USED IN LIEU OF METAL PLATES FOR MAS AND FULLY ADHERED SYSTEMS ONLY.

Firestone
 BUILDING PRODUCTS
 NOBODY COVERS YOU BETTER.™
 www.firestoneppco.com

BASE TIE-IN WITH QUICKSEAM RPF AND 2" METAL PLATES FASTENED TO DECK
 ULTRAPLY™ TPO ACCEPTABLE SYSTEMS: ALL

ISSUE / REVISION DATE:
 6/26/2014
 NOT TO SCALE

MAXIMUM WARRANTY: **20 YEARS**
 DETAIL NO.
UT-BT-3