



- NOTES:
1. REFER TO FIRESTONE WEBSITE FOR MOST CURRENT INFORMATION.
 2. REFER TO UT-LS-1 OR UT-LS-2 FOR WELD WIDTH.
 3. ULTRAPLY TPO FLASHING (UNSUPPORTED) MAY BE USED IN LIEU OF PRE-MOLDED ULTRAPLY TPO INSIDE/OUTSIDE CORNER FOR A MAXIMUM WARRANTY OF 15 YEARS.
 4. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO UT-LS-14 FOR CUT EDGE SEALANT APPLICATION.

ULTRAPLY TPO 18" CURB FLASHING OR MEMBRANE HEAT WELDED TO ULTRAPLY TPO FIELD SHEET (SEE NOTE #2 & #4)

PRE-MOLDED ULTRAPLY TPO INSIDE/OUTSIDE CORNER WELDED IN PLACE (SEE NOTE #3)

ULTRAPLY TPO MEMBRANE (FIELD SHEET).

MAXIMUM WARRANTY: **20 YEARS**

OUTSIDE CORNER

ULTRAPLY™ TPO

ACCEPTABLE SYSTEMS: ALL

ISSUE / REVISION
DATE:
7/01/2014

DETAIL NO.
UT-C-1

NOT TO SCALE