



- NOTES:
1. REFER TO FIRESTONE WEBSITE FOR MOST CURRENT INFORMATION.
 2. REFER TO DETAIL UT-LS-1, UT-LS-2, OR UT-LS-3 FOR WELD WIDTH.
 3. T-JOINT COVER REQUIRED FOR .060 GAUGE MEMBRANE ONLY.
 4. ULTRAPLY TPO FLASHING (UNSUPPORTED) (4x4" MIN. ROUNDED CORNERS) MAY BE USED IN LIEU OF T-JOINT CORNERS.
 5. WHEN REINFORCEMENT OF TPO MEMBRANE IS EXPOSED, REFER TO UT-LS-14 FOR CUT EDGE SEALANT APPLICATION.

Firestone
 BUILDING PRODUCTS
 NOBODY COVERS YOU BETTER.™
 www.firestonebpc.com

LAP SPICE WITH HEADLAP UNDER CURB OR WALL
FLASHING USING T-JOINT COVER
 ULTRAPLY™ TPO ACCEPTABLE SYSTEMS: ALL

ISSUE / REVISION
 DATE: 6/24/2014
 NOT TO SCALE

MAXIMUM WARRANTY: **20 YEARS**
 DETAIL NO.
UT-LS-10