



- NOTES:
1. REFER TO FIRESTONE WEBSITE FOR MOST CURRENT INFORMATION.
 2. NON-FIRESTONE METAL COPING IS ACCEPTABLE FOR USE IN THIS DETAIL PROVIDED FABRICATION AND INSTALLATION IS IN ACCORDANCE WITH CURRENT SMAGNA RECOMMENDATIONS. HOWEVER, WATERTIGHT INTEGRITY OF WALL AND METAL COPING SHALL BE ENSURED OTHERS AND BE EXCLUDED FROM WARRANTY COVERAGE IN THE THE EVENT NON-FIRESTONE COPING IS UTILIZED.
 3. WOOD NAILER MUST BE INSTALLED TO MEET APPLICABLE BUILDING CODES OR 200 LBS PER LINEAR FOOT IN ANY GIVEN DIRECTION.
 4. FASTEN COPING CLEAT AS PER SUPPLIED INSTRUCTIONS.

MAXIMUM WARRANTY: **20 YEARS**

TERMINATION AT TOP OF WALL WITH FIRESTONE COPING

ULTRAPLY™ TPO

ACCEPTABLE SYSTEMS: ALL

ISSUE / REVISION
DATE: 7/22/2014

DETAIL NO.
UT-T-12