



Coiled Metal Batten Strip

Firestone Item Number:
W56RAC3052: 25.4 mm (1.0") Wide

DESCRIPTION:

Firestone Coiled Metal Batten Strip is specifically designed to be used for anchoring approved Firestone membranes as specified in Firestone Specialty Products specifications and details. Coiled Metal Batten Strip is packaged in a weather-resistant cardboard dispensing package, which contains 67.06 m (220.0') of batten strip. Using Coiled Metal Batten Strips in lieu of conventional pre-cut strips reduces labor and storage space. Coiled Metal Batten Strip has 76.2 mm (3.0") o.c. pre-punched holes for greater flexibility in attaching to various substrates.

METHOD OF APPLICATION:

Attach batten strips to the substrate or penetration using the appropriate Firestone fastener. Do not overdrive or underdrive fasteners. Start at one end of the batten strip and fasten towards the other to reduce bowing between fasteners.

STORAGE:

Store in original unopened container protected from the weather until ready for use.

PACKAGING:

Firestone Coiled Metal Batten Strip is packaged 67.06 m (220.0') per coil and 52 coils per pallet.

PRECAUTIONARY DATA:

1. Do not overdrive or underdrive fastener.
2. All cut surfaces must be rounded and filed to remove burrs and sharp edges.
3. Use only on smooth surfaces.

LEED INFORMATION:

Post Consumer Recycled Content: 8%
 Post Industrial Recycled Content: 17%
 Manufacturing Location: Cleveland, OH



PRODUCT DATA

<u>Property</u>	<u>Minimum Performance</u>
Material:	Galvalume® AZ 55
Corrosion Resistance:	Meets FM No. 4470 criteria
Length:	67.06 m (220.0') per coil
Width:	25.4 mm (1.0")
Thickness:	1.13 mm/1.29 mm (0.0448"/0.0508")
Holes:	8.74 mm (0.344") diameter 76.2 mm (3.0") o.c. (Accommodates Firestone All-Purpose, Heavy-Duty, Heavy-Duty Plus and Concrete Drive Fasteners)
Weight:	14.5 kg (32 lb) per coil

Note: Galvalume® is a registered trademark of BIEC International, Inc.

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice design, Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any project on which its products may be applied. If questions arise as to the soundness of a project, or its ability to support a planned installation property, the Owner should obtain opinions of competent design engineers before proceeding. Firestone accepts no liability for any failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.