

QuickSeam™ Walkway Pad



Item Description

30" X 30" X .300"
(762 mm X 762 mm X 7.62 mm)

Item Number

W56RAC1860

Product Information

Description:

QuickSeam Walkway Pads are high quality rubber walkway pads with QuickSeam Tape factory laminated to the bottom surface. The QuickSeam Tape secures the walkway pads to the primed RubberGard™ EPDM membrane.

QuickSeam Walkway Pads help protect the membrane from damage due to necessary rooftop service traffic. The material exhibits excellent levels of hardness, tensile strength, wear and tear resistance, and displays excellent cold flexibility.

The owner is responsible for maintaining walkways in specific areas:

- At all access points (ladders, hatches, doorways, etc.) to the roof.
- Around all mechanical equipment which will require maintenance.
- As a walkway system on roofs subjected to traffic more frequently than once per month.

Method of Application:

1. Position the QuickSeam Walkway pads so that the flat surface is over the completed RubberGard EPDM membrane, spacing each pad a minimum of 1" (25.4 mm) and a maximum 6" (152.4 mm) from each other to allow for drainage.
2. If installation of the QuickSeam Walkway Pads is over field fabricated seams, or within 3" (76.2 mm) of a lap edge, the seam must be stripped in using 6" (152.4 mm) QuickSeam Batten Cover. Apply the 6" QuickSeam Batten Cover Strip a distance of 6" (152.4 mm) minimum past each side of the walkway pad over the field seam.
3. Use QuickPrime™ Plus, QuickPrime Plus LVOC, Single Ply QuickPrime Primer, or Single-Ply LVOC Primer, applied with a QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime the RubberGard membrane.
4. Allow primer to dry per the touch-push test.
5. Remove the release liner on the tape and place the taped walkway pad into place on the primed membrane.
6. Walk on the pad to assure proper overall adhesion.

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of two years can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Precautions:

- Refer to Safety Data Sheet (SDS).
- When installing walkway pads on a ballasted system, additional ballast must be added around pads to maintain 10 lb/ft² (48.82 kg/m²).

TECHNICAL INFORMATION SHEET

QuickSeam™ Walkway Pad

Precautions Continued:

- Do not install walkway pads within 10' (3.05 m) of a roof edge when used in conjunction with ballasted systems. Concrete paving stones must be used in these areas.
- Do not expose to open flame or ignition source.
- Primers may have an adverse affect on polystyrene insulations.
- Do not install black QuickSeam Walkway Pads on UltraPly TPO membranes.

LEED® Information:

Post Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: Guelph, ON – Canada; Wapakoneta, OH - USA
 *NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Packaging:

50 pads per pallet; 445 lb/pallet (201.9 kg/pallet)

Typical Properties – QuickSeam Tape

<u>Property</u>	<u>Value</u>
Base	Rubber Polymers
Color	Black
Solvents	None
Solids	100%
Cured State	Cured
Thickness	0.030" (0.77 mm) ± 0.005" (0.127 mm)

NOTE: QuickSeam Tape is factory laminated to walkway pads: 3 rows of 3" (76.2 mm) wide tape, or two rows of 7" (177.8 mm) wide tape.

Typical Properties – Walkway Pad

<u>Property</u>	<u>ASTM Test Method</u>	<u>Minimum Performance</u>	<u>Value</u>
Base	---	---	Rubber Polymers
Elongation, % min:			
<i>Parallel to grain flow</i>	---	75	---
<i>Perpendicular to grain flow</i>	--	75	---
Brittleness Temperature	D 2137	40 °F (-40 °C)	---
Hardness, Shore A	D2240	60 ± 5	---

Please contact Quality Building Services Technical Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.