

QuickSeam™ Penetration Pocket Kit

Item Description

QuickSeam 6" (152 mm) dia.
QuickSeam 10" (254 mm) dia.

Item Number

W56RACQS06
W56RACQS10



Product Information

Description:

QS Penetration Pockets are a labor saving alternative to conventional penetration pockets. QS Penetration pockets are produced using injection molding technology, ensuring uniform product quality and consistency part after part. Each Penetration Pocket is produced with factory laminated QuickSeam Tape, simplifying installation to RubberGard™ EPDM.

Method of Application:

1. Remove existing flashing materials, rust, dirt etc. from penetration prior to installing the QS Penetration Pocket.
2. Seal around the penetration prior to installation to prevent Pourable Sealer from flowing into the roof system and possibly into the building.
3. Prime the penetration and the roof membrane with appropriate primer.
4. Apply QuickPrime™ Plus; QuickPrime Plus LVOC; Single-Ply LVOC Primer; or Single-Ply QuickPrime Primer to the inside of the plastic reinforcing ring.
5. After the primer has dried, position the plastic ring centered around the penetration and place on the primed EPDM. Each plastic ring is split to allow application around penetrations. Ensure there is a minimum of 1" (25.4 mm) clearance between the penetration's perimeter inside the plastic ring. If 1" (25.4 mm) clearance cannot be achieved a larger field fabricated penetration pocket must be used.
6. If necessary to cut the QS Penetration Pocket to apply around the penetration, cut along the line indicated on the flange and side wall.
7. With the release paper intact, place the pocket around the plastic ring so that the top lip of the pocket covers the plastic ring.
8. Locate the pre-cut area of the paper on the underside of the flange and remove a small area of the paper closest to the ring.
9. Using hand pressure, attach the inside of the flange to the membrane to insure the pocket doesn't move while removing the remainder of the paper.
10. Remove the remainder of the release paper and roll the flange from the inside to the outside edge using a rubber seam roller.
11. Flash any cuts in QS Penetration Pocket kit with QuickSeam Flashing (not included in kit). Prime all surfaces to receive QS Flashing to cover cuts.
12. Install Pourable Sealer S-6, 10 or FillGard M Pourable Sealer inside QS Penetration Pocket kit, taking care to mound the Pourable Sealer so water cascades and flows away from the sealed penetration.
13. Apply Lap Sealant HS at all exposed lap edges in QS Penetration Pocket, QS Flashing, and any patches made in EPDM membrane to accommodate the roof penetration

NOTE: Typically the roof membrane has been cut to accommodate the penetration. Before installing the QS Penetration Pocket, repair the cut per Firestone specifications, extending the patch to the penetration itself.

QuickSeam™ Penetration Pocket Kit

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of two (2) years can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Precautions:

Refer to Safety Data Sheets (SDS).

Coverage Rate:

QuickSeam 6: Accommodates penetrations up to 4" (101 mm) outside diameter

QuickSeam 10: Accommodates penetrations up to 8" (203 mm) outside diameter

LEED® Information:

Post Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Bensenville, IL

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Packaging

Property	Value
Kit Contents:	6 Molded EPDM Penetration Pockets with factory applied QuickSeam tape 6 Plastic reinforcing rings 2 Stir Sticks 1 QuickSeam Pad and Handle NOTE: Firestone Pourable Sealer, QuickSeam Flashing, and necessary primers and caulks are not included in each kit and must be purchased separately.
Kit:	6 Penetration Pockets/Kit
Pallet:	40 Kits per Pallet
Weight:	<u>QuickSeam 6:</u> 6.5 lb (2.95 kg)/Kit 260 lb (118.2 kg)/Pallet <u>QuickSeam 10:</u> 7.0 lb (3.18 kg)/Kit 280 lb (127.2 kg)/Pallet

QuickSeam™ Penetration Pocket Kit

Typical Properties

<u>QuickSeam Tape (on QuickSeam Penetration Pocket Flange):</u>	<u>Value</u>
Base	Rubber Polymers
Color	Black
Solvents	None
Solids	100%
Cured State	Cured
Thickness	0.030" (076 mm)
<u>Stir Stick:</u>	<u>Value</u>
Material	Recycled Plastic
Color	Red
<u>Plastic Ring:</u>	<u>Value</u>
Material	Schedule 40 PVC
Color	White or Black
Shape	Round, pre-cut in one place; supports QuickSeam Penetration pocket
Size	<u>QuickSeam 6:</u> 6" (152 mm) inside diameter, 2" (50 mm) high, 0.31" (8 mm) wall thickness <u>QuickSeam 10:</u> 10" (254 mm) inside diameter, 2" (50 mm) high, 0.31" (8 mm) wall thickness
<u>QuickSeam Penetration Pocket:</u>	<u>Value</u>
Material	Injection Molded EPDM
Color	Black
Size	<u>QuickSeam 6:</u> 6.7" (170 mm) inside diameter, 2" (50 mm) high, 0.060" (1.1 mm) thick with 3" (76 mm) pre-taped flange <u>QuickSeam 10:</u> 10.7" (271 mm) inside diameter, 2" (50 mm) high, 0.060" (1.1 mm) thick with 2.5" (63.5 mm) pre-taped flange

Please contact Quality Building Services Technical Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.