

# TECHNICAL INFORMATION SHEET

## UltraPly™ TPO QuickSeam™ Flashing



### Item Description

White  
Gray  
Tan

### Item Number

W56TPO30T7  
W56TPOG0T7  
W56TPOT0T7

## Product Information

### Description:

UltraPly TPO QuickSeam Flashing is a non-reinforced TPO membrane factory laminated to white seam tape. TPO QuickSeam Flashing is used for flashing applications as indicated in the Firestone Technical Manual.

### Method of Application:

1. Use Firestone Single Ply QuickPrime™ Primer or Single Ply LVOC Primer applied using QuickScrubber™ or QuickScrubber Plus to clean and prime membrane and metal mating surfaces to receive UltraPly QuickSeam Flashing.
2. Refer to Firestone Technical Database for application instructions and details using Firestone UltraPly TPO QuickSeam Flashing: [www.technicaldatabase.fsbp.com](http://www.technicaldatabase.fsbp.com)
3. Refer to application instructions for specifics.

### Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of 1.5 years can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

### Precautions:

Refer to Safety Data Sheet (SDS) for more information.

### LEED® Information:

Post Consumer Recycled Content: 0%  
Post Industrial Recycled Content: 0%  
Manufacturing Location: Michigan Center, MI  
\*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.



## Packaging

<u>Property</u>	<u>Value</u>
Roll:	5.5" (140 mm) x 100' (30.48 m) roll
Carton:	2 rolls per carton

NOTE: QuickScrubber and/or QuickScrubber Plus Pads and Handles are included in each carton. Quantities vary depending on the QuickSeam product.

## UltraPly™ TPO QuickSeam™ Flashing

### Typical Properties

QUICKSEAM TAPE		TPO FLASHING	
<u>Property</u>	<u>Value</u>	<u>Property</u>	<u>Value</u>
Base:	Rubber Polymers	Base	TPO
Color:	White	Color	White, Gray, Tan
Percent Solids:	100%	Solvents:	None
Specific Gravity:	1.08 ± 0.03	Solids:	100%
Cured State:	Cured	Specific Gravity:	0.96 ± 0.02
Thickness:	0.030" (0.76 mm) ± .005" (0.13 mm)	Thickness	0.030"(0.76 mm) ± 10%
Width:	5¾" (140 mm) -0 /+ 1/16" (1.6 mm)	Width:	5½" (140 mm) +0 / - ¼" (3.18 mm)
Length:	100' (30.5 m)	Length:	100' (30.5 m)

Please contact your Firestone Building System Advisor at 1-800-428-4511 for further information.

*This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.*