

UltraPly™ TPO Universal QuickSeam™ Pipe Flashing

Item Description
Pipe Flashing

Item Number
W56TPO3033



Product Information

Description:

UltraPly QuickSeam Pipe Boots are specifically designed to be used in roofing applications for flashing of round penetrations in UltraPly TPO roofing systems. UltraPly QuickSeam Pipe Boots fit various penetrations and must be cut to correct pipe diameter before installation.

Method of Application:

1. Prepare the UltraPly TPO membrane to receive tape using Single-Ply QuickPrime™ Primer, Single-Ply QuickPrime LVOC Primer, and a QuickScrubber™ or QuickScrubber Plus pad and handle to remove all dust, dirt and other contaminants that will affect the finished bond.
2. Allow to dry according to the touch-push test.
3. Cut along the top portion of the UltraPly QuickSeam Pipe Flashing corresponding to the size of the pipe.
4. To ensure conformability slightly heat the surface of the TPO membrane using a hot air welder.
5. Install the Pipe Flashing, clamping ring and UltraPly General Purpose Sealant per Firestone Specifications and Details.
6. Roll flashing to conform into any step-offs.

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (26.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

Shelf Life:

- Shelf life of two years can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Precautions:

- Do not install on uneven substrates.
- Refer to Safety Data Sheet (SDS).

LEED® Information:

Post Consumer Recycled Content: 0%
Post Industrial Recycled Content: 0%
Manufacturing Location: Bensenville, IL

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

UltraPly™ TPO Universal QuickSeam™ Pipe Flashing

Fit Guidelines

Fits the pipe outside diameter shown below		NOTE: Make cut above rib.
Property	Value	
1"	25 mm	
1½"	38 mm	
2"	50 mm	
3"	76 mm	
4"	102 mm	
5"	127 mm	
6"	152 mm	

Typical Properties

Molded Pipe Flashing		QuickSeam Tape	
Property	Value	Property	Value
Base	Thermoplastic Polyolefin (TPO)	Base	Rubber Polymer
Color	White	Color	White
Sizes	Universal – Fits 1- 6" Ø (25 – 74 mm)	Solvents	None
Clamp	Stainless Steel – worm gear type (clamps not included)	Percent Solids	100%
Pipe Flange	13" (33 cm) outside diameter	Cured State	Cured
Thickness	0.055-0.075" (1.4 -1.9 mm)	Thickness	0.030" (0.762 mm) + 0.005" (0.13 mm)

Please contact Quality Building Services Technical Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.