

TECHNICAL INFORMATION SHEET

EcoWhite™ QuickSeam™ Splice Tape



Item Description

3" x 100' (76.2 mm x 30.48 m)
6" x 100' (152.4 mm 30.48 m)

Item Number

W56RAC160B
W56RAC160E

Product Information

Description:

Firestone EcoWhite EPDM 3" (76.2 mm) and 6" (152.4 mm) QuickSeam Splice Tape is designed for field splicing of EcoWhite EPDM membrane panels and flashing.

Method of Application:

1. Use Single-Ply QuickPrime™ Primer or Single-Ply LVOC Primer with a QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime mating surfaces.
2. Refer to application instructions for specifics: Technical Database, www.firestonebpc.com

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 100 °F (37.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of two years can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Precautions:

Refer to the Safety Data Sheet (SDS) for further information.

Packaging:

Roll: 3" x 100' (76.2 mm x 30.48 m) roll, 4 rolls per carton; 6" x 100' (152.4 mm 30.48 m) roll, 2 rolls per carton

NOTE: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton.

Quantities vary depending on the QuickSeam product.

LEED® Information:

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Michigan Center, MI

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.



Typical Properties

Property	Value
Base:	Rubber Polymers
Color:	White
Solvents:	None
Solids:	100%
Cured State:	Cured
Thickness:	0.030" (0.77 mm) ± 0.005" (0.127 mm)

Please contact Firestone Technical Services Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.