

TECHNICAL INFORMATION SHEET

V-Plate

Item Description
Pail: 500 Pieces

Item Number
W56RAC4182



Product Information

Description:

The Firestone V-Plate is specifically designed to be used with Firestone All-Purpose, Heavy Duty and Concrete Drive fasteners. The V-Plate is used to anchor Firestone RubberGard™ MAX membrane, Firestone Reinforced Perimeter (RPF) Strip (RPF) and QuickSeam™ Reinforced Perimeter (RPF) Strips, and Firestone QuickSeam R.M.A. Strip as shown in Firestone Specifications and Details.

Product Packaging

Pail:	500 pieces
Pail Weight:	28lb (12.7 kg) per pail
Pallet:	80 pails

Method of Application:

RubberGard MAX Membrane:

The V-Plate is installed in the seam and is specifically designed for 7" (177.8 mm) or 6" (152.4 mm) QuickSeam Tape applications as specified by Firestone Specifications and Details. Position the plates 3-1/2" (88.9 mm) in from the panel edge at the required spacing and anchor with the appropriate length Firestone fastener.

QuickSeam RPF, QuickSeam R.M.A. Strips and RPF Strips:

The V-Plate shall be positioned on the applicable strip as specified in Firestone Specifications and Details. Attach the V-Plate to roof deck using the appropriate length Firestone fastener.

Storage:

Store in unopened original containers protected from the weather.

Precautions:

1. Do not overdrive or underdrive fastener.
2. Plates are not to be used for insulation attachment or attachment of **non-reinforced membrane**.
3. **Cannot be used with Firestone Heavy Duty (HD) Plus Fasteners.**

LEED® Information:

Postconsumer Recycled Content: 8%
Preconsumer Recycled Content: 17%
Manufacturing Location: Cleveland, OH



TECHNICAL INFORMATION SHEET

V-Plate

Physical Properties

<u>Property</u>	<u>Typical Performance</u>
Material:	Commercial Quality (CQ) grade steel with AZ55 Galvalume® coating
Material Thickness:	0.033" (0.84 mm) - 0.039" (0.99mm)
Diameter:	2-1/4" (57 mm)
Corrosion Resistant Coating:	Meets FM No. 4470 Criteria
Pull Through Resistance:	400 lbf (181.4 kgf) from center hole

Galvalume® is a registered trademark of BIEC International, Inc.

Please contact your Firestone Roof Systems Advisor at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.