



NOTES:

1. REFER TO FIRESTONE WEBSITE FOR MOST CURRENT INFORMATION.
2. MAXIMUM 6" (152 mm) LONG FASTENERS (NOTE: WOOD BLOCKING MAY BE SUBSTITUTED FOR INSULATION TO REDUCE FASTENER LENGTH REQUIREMENT).
3. BONDING ADHESIVE REQUIRED BETWEEN MEMBRANE AND INSULATION FOR FULLY ADHERED SYSTEMS.
4. BATTEN STRIP MAY BE USED IN LIEU OF PLATES FOR MAS AND FULLY ADHERED SYSTEM ONLY. REFER TO "UT-BT" DETAILS FOR SPECIFIC BASE TIE-IN INFORMATION, REQUIREMENTS, AND OPTIONS.

Firestone
 BUILDING PRODUCTS
 NOBODY COVERS YOU BETTER.™
 www.firestonebpc.com

TERMINATION AT R.T.U. WITH QUICKSEAM RPF (UNIT FLANGE MOUNTED TO SUBSTRATE)

ULTRAPLY™ TPO

ACCEPTABLE SYSTEMS: ALL

ISSUE / REVISION DATE:
 7/24/2014

MAXIMUM WARRANTY: **20 YEARS**

DETAIL NO.
UT-T-16

NOT TO SCALE