

# TECHNICAL INFORMATION SHEET

## White One-Part Pourable Sealer

**Item Description**

White One-Part Pourable Sealer

- 2 L Pouch, 4 Pouches per Carton

**Item Number**

W563587080

One-Part Pourable Sealer Nozzle

- 40 Nozzles per Carton

W563587081

### Product Information

**Description:**

An easy to dispense White One-Part Pourable Sealer packaged in re-sealable pouches designed to seal penetrations inside penetration pockets where allowed by Firestone details. An excellent product for sealing field made pitch pans and penetration pockets.

**Method of Application:**

1. Substrates to receive White One-Part Pourable Sealer must be free of moisture, dust, dirt, oil, and any other contaminants.
2. Make sure the penetration to be sealed is watertight.
3. After preparation of the penetration pocket per Firestone details, apply an approved Firestone primer to all surfaces that will come into contact with White One-Part Pourable Sealer. Allow primer to flash off before dispensing sealer.
4. Remove the cap from the White One-Part Pourable Sealer and dispense into the penetration pocket by rolling the pouch from back to front. Utilize One-Part Pourable Sealer Nozzle (W563587081) if needed to aid in application.
5. Fill penetration pocket to a minimum depth of 2" (51 mm) and mound sealer to shed water away from the actual penetration.
6. Take care not to trap air when resealing pouch.

**Storage:**

- Store in original unopened containers, at temperatures between 60 °F and 80 °F (15.6 °C and 26.7 °C) until ready for use. Do not store in direct sunlight.
- When exposed to lower temperatures, restore to room temperature prior to use.
- Keep stored material dry.

**Shelf Life:**

- Shelf life of one year can be expected when stored in original sealed containers at temperatures between 60 °F and 80 °F (15.6 °C and 26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.
- White One-Part Pourable Sealer is a moisture-cure product, and will start to cure within the pouch after the initial opening of the pouch. Use contents within 30 days after initial pouch opening.

**Coverage Rate:**

Coverage rate of 122 in<sup>3</sup> (2000 cm<sup>3</sup>) per pouch.

# TECHNICAL INFORMATION SHEET

## White One-Part Pourable Sealer

### Precautions:

- Review Safety Data Sheet (SDS) prior to use.
- Keep away from fire and open flame during storage and use.
- Avoid moisture contamination during storage. White One-Part Pourable Sealer is a moisture-cure product, and will start to cure within the pouch after the initial opening of the pouch.
- Use contents within 30 days after initial pouch opening.
- Do not thin.
- Do not contaminate with foreign materials.
- Avoid contact with eyes. Eye protection must be worn during installation.
- Avoid contact with skin. White One-Part Pourable Sealer is extremely difficult to remove. Disposable gloves are recommended when dispensing White One-Part Pourable Sealer.
- Avoid breathing vapors. Use only in well ventilated areas.
- Re-seal pouch tightly when not in use.

### LEED® Information:

Post-Consumer Recycled Content: 0%  
 Post Industrial Recycled Content: 0%  
 Manufacturing Location: Spring Lake, MI  
 \*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

### Typical Properties

<u>Property</u>	<u>Typical Performance</u>
Base:	Polyurethane
Color:	White
Solids by Volume:	99.5%
Specified Gravity:	1.48
Density:	12.3 lb/gal
Pot Life:	60 minutes
V.O.C. Content:	EPA test method 24 < 13 g/L (0.11 lb/gal)

Please contact Firestone Technical Services Department at 1-800-428-4511 for further information.

*This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.*